



富通塑化科技(控股)有限公司

FUTON PETRO CHEMICAL TECHNOLOGY (HOLDINGS) LIMITED

香港灣仔洛克道者220號洛洋閣商業大廈23樓B室

Rm B,23/F.,Loyong Court Comm.Bldg. 212-220 Lockhart Road,Wanchai,HK.

Tel: (755)8429 4482 Fax: (755)8429 4483 E-Mail:Aaron@futontape.com.cn

PRODUCT CATALOG

CODE NO	PRODUCT	DESCRIPTION	SPECIFIC DETAIL	PRODUCT PICTURE
FUTON-001	OPP PACKING (GUMMED)TAPE	<p>Carton packing tape are made from thin sheets of bioriented polypropylene (BOPP) which serves as the backing material. These backing materials are then coated with various thicknesses of acrylic adhesives for different weighting requirements. And according to the season, different temperature range tapes can be elected.</p> <p>Since BOPP tapes posses the unique quality of being light weight, nonstretchable, they therefore have been widely adopted in automated carton packing machinery throughout the industries</p>	<p>Thickness:35-65mic with water base acrylic glue width:12-150mm length:20-1100m inner core:3" paper core ,can be printed with logo various colors available: clear,tan/brown/coffee,stuff.etc.Can be printed with 4 colour pattern stand shrink or flat shrink according to the standard</p>	
FUTON-002	LLDPE STRETCH (PALLET) FILM	<p>LLDPE Stretch Film, is widely used in pallet packing of bulk goods during transportation or warehouse storage Lightweight, strong tenacity, excellent puncture resistance Good self-adhesive</p>	<p>Thickness:15-50mic,made of recycled materials, reusable width:300mm-500mm colour:transparent or black 2"(50mm) or 3"(75mm) paper core Grade: Hand use, semi-automatic machine use, auto-machine use</p>	



富通塑化科技(控股)有限公司

FUTON PETRO CHEMICAL TECHNOLOGY (HOLDINGS) LIMITED

香港灣仔洛克道者220號洛洋閣商業大廈23樓B室

Rm B,23/F.,Loyong Court Comm.Bldg. 212-220 Lockhart Road,Wanchai,HK.

Tel: (755)8429 4482 Fax: (755)8429 4483 E-Mail:Aaron@futontape.com.cn

PRODUCT CATALOG

FUTON-003	STATIONERY TAPE	<p>Stationery tape is made out of BOPP and coated with water based acrylic glue . It could be printed any logo in it, it could be made into easy to tear and hard to tear and made into invisible also. Stionery tape is widely used for ordinary office packing and school fixing or combination and it is also good for super market sales</p>	<p>Thickness:35-65mic with water base acrylic glue width:12mm,15mm,17mm,18mm,24mm etc colour:transparent,tan/brown,coffee,stuff,etc; 3" paper core ,can be printed with colourful logo or 2" platic core. packing:standing pack or flat pack according to the</p>	
FUTON-004	OPP JUMBO ROLL	<p>Thin sheets of bioriented polypropylene (BOPP) which serves as the backing material. These backing materials are then coated with various thicknesses of acrylic adhesives for different weighting requirements.It is popular for clients who already have adhesive tape slitting machines.</p>	<p>Thickness:35-65mic with water base acrylic glue width:0.98m,10.4m,1.28m,1.6m length:4000m colour:transparent,tan/brown/coffee,stuff,or for the client's require bubble sheet and corrugate paper coated for export packaging</p>	



富通塑化科技(控股)有限公司

FUTON PETRO CHEMICAL TECHNOLOGY (HOLDINGS) LIMITED

香港灣仔洛克道者220號洛洋閣商業大廈23樓B室

Rm B,23/F.,Loyong Court Comm.Bldg. 212-220 Lockhart Road,Wanchai,HK.

Tel: (755)8429 4482 Fax: (755)8429 4483 E-Mail:Aaron@futontape.com.cn

PRODUCT CATALOG

<p>FUTON-005</p>	<p>MASKING TAPE</p>	<p>Masking tape is made from crepe paper as the backing material which is coated with rubber based adhesive. The adhesive is formulated so that it leaves no traces after removing the tape. Widely applied to household and industry for bunding, sealing, holding surface protection Protection of mirror or glass edges against hurting people</p>	<p>Thickness:130,145mic etc. The temperature: 60 degree(normal use), 80 degree(automobile use), 120 degree. Can be special packed as request</p>	
<p>FUTON-006</p>	<p>DOUBLE -SIDE TAPE</p>	<p>It's made with tissue paper as the backing material. As the double sided terms implies, the tapes use solvent based, water based, hot melt based adhesive to coat both sides of backing material. They are then pressed on to release paper for separation purposes It's characterized by excellent thickness, easy tear and good adhesion, suitable for decoration, sealing documents, postal service and shoe making industry. Best choice for the office, home and school</p>	<p>Thickness:80mic,90mic,100mic width:24mm,48mm etc can be special packed as request</p>	



富通塑化科技(控股)有限公司

FUTON PETRO CHEMICAL TECHNOLOGY (HOLDINGS) LIMITED

香港灣仔洛克道者220號洛洋閣商業大廈23樓B室

Rm B,23/F.,Loyong Court Comm.Bldg. 212-220 Lockhart Road,Wanchai,HK.

Tel: (755)8429 4482 Fax: (755)8429 4483 E-Mail:Aaron@futontape.com.cn

PRODUCT CATALOG

FUTON-007	CLOTH DUCT TAPE	Take textile fibre colth as the backing material, It is designed for the reinforced protection of various pipes and objects	Backing Carrier: textile fiber cloth and PE Adhesive: hot melt Mesh: 35, 50, 70 Thickness, Width and length: according to clients' requests Excellent initial tack Water and moisture proof Suitable for the reinforced protection of pipes, objects and heavy weight sealing tasks Carrier: textile fiber cloth	
FUTON-008	KRAFT PAPER TAPE	kraft paper tape are most frequently used for packaging, carton sealing, is activated by water. High adhesion, strong tensile strength. Sealing all carton, steadying and bundling.	Coated with heat-melt PSAs (or rubber PSAs) onto kraft paper, the tapes are designed for package. Thickness: 135mic-160mic Length: 20m-60m Width: 12mm-48mm Color: (it can be bear 130), yellow	
FUTON-009	PVC INSULATION TAPE	Take PVC film as its backing material, coated with Acrylic solvent glue, have wonderful proformance in wire/cable/ wrapping. insulation, flame retardancy, cold resistance, voltage resistance, acid and alkali resistance, and solvent resistance.	Specification: 0.13mm x 19mm x 10yds; 0.13mm x 19mm x 20yds; 0.15mm x 19mm x 20yds; 7mil x 3/4" x 60ft.	



富通塑化科技(控股)有限公司

FUTON PETRO CHEMICAL TECHNOLOGY (HOLDINGS) LIMITED

香港灣仔洛克道者220號洛洋閣商業大廈23樓B室

Rm B,23/F.,Loyong Court Comm.Bldg. 212-220 Lockhart Road,Wanchai,HK.

Tel: (755)8429 4482 Fax: (755)8429 4483 E-Mail:Aaron@futonape.com.cn

PRODUCT CATALOG

Contact information:

SALES DEPARTMENT

FUTON (SHENZHEN) ADHESIVE PRODUCTS CO.,LTD

FUTON PETRO CHEMICAL TECHNOLOGY (HOLDINGS) LTD

ADD:NO 280A,XINSHENG RD, LONGGANG DIST,

518116 SHENZHEN,P.R.C

TEL:+86 (0)755 84294482 EXT 842

FAX:+86 (0)755 84294483

CELL:86 13424151249

BUSINESS EMAIL:Aaron@futonape.com.cn

OR EMAIL:Aaroncatzx@hotmail.com

WEBSITE:<http://futonape.tradeprince.com/>

<http://www.futonape.com.cn/>

MSN:aaroncatzx@hotmail.com

YAHOO:aaron_zhong84

SKYPE:aaroncatzx